MESKER DOOR - ORDER FORM: FRAMES

Series:	Component:	Type:	Steel type:	Ends/corners:	Welded / anchors	Hdw. Locations	Hdw: see tabs for more	
F = masonry	FH = header	DR = unequal rab.	- = CRS	Notch	1 = tacked in ZEE's	- = Mesker	U = ASA	H = interconnected strike
FDJ = drywall	HJ = hinge jamb	ER = equal rab.	Z = GALV	Miter	2 = P&D hole	SCT = Steelcraft	C = T Strike	VRM = CVR strike
RF = remodeling	SJ = strike jamb	SR = single rab.	G90 = G90	Face weld	3 = P&D+Tube	AMW = Amweld	DBS = deadbolt	ELS = electric strike
FF = flush face	BJ = blank strike	DE = dbl. eggress		Full weld	4 = AEW hole only	CEC = Ceco	RL = roller latch	EH = electric hinge
S = stick	WJ = window	CO = cased open			5 = AEW	CUR = Curries	RPR = rim reinf.	4H = 4.5" Hvy. Wt. hinges
M = mullion	BS = blank stick	C = communicating	Face:	Thickness:	6 = Adjustable flr.	PNR = Pioneer	VRR = v. rod reinf.	5 = 5" hinges
	BM = blank mull	RF = Remodeling	- = 2"	4 = 1 3/4	7 = other	DNS = Dean Steel	FB = flush bolt	5H = 5" Hvy. Wt. hinges
	HS = Hinge stick		W4F = 4"	8 = 1 3/8	- = none	ZZZ = Custom	RA = reg. arm closer reinf.	The default qty of Std. Wt. 4.5" sq. hinge preps will be assumed without needing a code
	HM = Hinge M			0 = no pocket	Loose anchors ordered seperately	DD = Dutch	PA = P. arm closer reinf.	
	S(S/M)=Strike S or M					DDA = Dutch ADA	BR = cont. hinge reinf.	

QTY	DOOR #	SERIES	COMPONENT	DEPTH	DEPTH: FRACTION	SIZE: NOMINAL	FRAME TYPE	STEEL TYPE	THICKNESS	GAUGE	HDW PREPS / REINFORCEMENTS	HDW. LOCATIONS	FACE	RETURNS	WELDED ANCHORS	ENDS / CORNERS	FIRE LABEL	APPLY DOOR # (Y/N)	HANDING	NOTES

Submit